

Printing date 02/27/2018

Version: 3

Reviewed on 02/27/2018

## 1 Identification

- · Product identifier
- · Trade name: <u>Ultra Setting Vaporizer</u>
- · Article number: 09292
- Application of the substance / the mixture make-up artist supplies
- Details of the supplier of the safety data sheet
- *Manufacturer/Supplier: Kryolan GmbH Papierstraβe 10 D-13409 Berlin Tel: 49 (0) 30499892-0 Fax: 49 (0) 304914994*
- Information department: Section Productsafty andreas.lueth@kryolan.de • Emergency telephone number: 49 (0)30499892-0

## 2 Hazard(s) identification

· Classification of the substance or mixture

H319

GHS02 Flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated.

GHS07

Causes serious eye irritation.

- *Eye Irrit. 2A* • *Label elements*
- · GHS label elements
- *The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms*



#### · Signal word Danger · Hazard statements H222-H229 Extremely flammable aerosol. Pressurized container: May burst if heated. H319 Causes serious eye irritation. · Precautionary statements P102 Keep out of reach of children. P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use. P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

US

45-55%

35-40%



#### Safety Data Sheet acc. to OSHA HCS

Reviewed on 02/27/2018

Printing date 02/27/2018

Version: 3

Trade name: Ultra Setting Vaporizer

(Contd. of page 1) · Classification system: · NFPA ratings (scale 0 - 4) Health = 2Fire = 0*Reactivity* = 3· HMIS-ratings (scale 0 - 4) HEALTH \*2 Health = \*2FIRE 0 Fire = 0*Reactivity* = 3**REACTIVITY** 3 · Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

#### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

## · Dangerous components:

- 115-10-6 dimethyl ether
- 64-17-5 ethanol

## 4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- Protective equipment: Wear self-contained respiratory protective device.
- · Additional information Cool endangered receptacles with water spray.

## 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Keep away from ignition sources
- $\cdot \textit{Environmental precautions: } Do not allow to enter sewers/ surface or ground water.$
- Methods and material for containment and cleaning up: Ensure adequate ventilation.

(Contd. on page 3)

US



Printing date 02/27/2018

Version: 3

Reviewed on 02/27/2018

Trade name: Ultra Setting Vaporizer

(Contd. of page 2)

• **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

## 7 Handling and storage

· Handling:

- **Precautions for safe handling** Use only in well ventilated areas. Keep away from heat and direct sunlight.
- *Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurized containers.
- · Information about storage in one common storage facility: Store away from flammable substances.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Storage class: 2 B
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

#### 115-10-6 dimethyl ether

WEEL 1000 ppm

64-17-5 ethanol

- PEL 1900 mg/m<sup>3</sup>, 1000 ppm
- *REL* 1900 mg/m<sup>3</sup>, 1000 ppm
- TLV Short-term value: 1880 mg/m<sup>3</sup>, NIC-1000 ppm Long-term value: 1880 mg/m<sup>3</sup>, 1000 ppm NIC-A3

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.
  Breathing equipment:
- Not necessary if room is well-ventilated.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:

Not required.

(Contd. on page 4)

<sup>·</sup>U

**KRYOLAN** 


Safety Data Sheet acc. to OSHA HCS

Printing date 02/27/2018

Version: 3

Reviewed on 02/27/2018

Trade name: Ultra Setting Vaporizer



Appearance:				
Form:	Aerosol Colorless Aromatic			
Color:				
Odor:				
Odor threshold:	Not determined.			
pH-value:	Not determined.			
Change in condition				
Melting point/Melting range:	Undetermined.			
Boiling point/Boiling range:	Not applicable, as aerosol.			
Flash point:	Not applicable, as aerosol.			
Flammability (solid, gaseous):	Extremely flammable liquefied gas.			
Ignition temperature:	235 °C (455 °F)			
Decomposition temperature:	Not determined.			
Auto igniting:	Product is not selfigniting.			
Danger of explosion:	Not determined.			
Explosion limits:				
Lower:	3,0 Vol %			
Upper:	18,6 Vol %			
Vapor pressure at 20 $\bullet C$ (68 $\bullet F$ ):	5200 hPa (3,900.3 mm Hg)			
Density at 20 °C (68 °F):	0,59 g/cm <sup>3</sup> (4.92355 lbs/gal)			
Relative density	Not determined.			
Vapor density	Not determined.			
Evaporation rate	Not applicable.			



Printing date 02/27/2018

Version: 3

Reviewed on 02/27/2018

Trade name: Ultra Setting Vaporizer

		(Contd. of page 4
· Solubility in / Miscibility with		
Water:	Partly miscible.	
· Partition coefficient (n-octand	ol/water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	74-82 %	
Water:	10-15 %	
VOC content:	78,7 %	
Solids content:	5-10 %	
• Other information	No further relevant information available.	

## 10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided:

Beware: Container is pressurized. Keep away from direct sun exposure and temperatures over 50°C. Do not open by force or throw into fire even after use.

· Possibility of hazardous reactions Danger of receptacles bursting because of high vapor pressure if heated.

• *Conditions to avoid No further relevant information available.* 

 $\cdot \textit{Incompatible materials: } No further relevant information available.$ 

· Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

Oral	LD50	5045 mg/kg (rat)
Dermal	LD50	12800 mg/kg (rabbit)

Inhalative LC50/4 h 30 mg/l (rat)

## · Primary irritant effect:

• on the skin: No irritant effect.

• on the eye: Irritating effect.

• Sensitization: No sensitizing effects known.

 $\cdot$  Additional toxicological information:

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

 $\cdot$  IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 6)

US



Version: 3

Reviewed on 02/27/2018

Trade name: Ultra Setting Vaporizer

Printing date 02/27/2018

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- *Bioaccumulative potential* No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- *Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

## 14 Transport information

· UN "Model Regulation": UN1950, AEROSOLS, 2.1

#### 15 Regulatory information

- $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara
- Section 355 (extremely hazardous substances):
- None of the ingredients is listed.
- Section 313 (Specific toxic chemical listings):
- None of the ingredients is listed.
- TSCA (Toxic Substances Control Act):
- All ingredients are listed.
- · Proposition 65
- · Chemicals known to cause cancer:
- None of the ingredients is listed.
- · Chemicals known to cause reproductive toxicity for females:
- None of the ingredients is listed.

(Contd. on page 7)

(Contd. of page 5)

US -



Version: 3

Reviewed on 02/27/2018

(Contd. of page 6)

A3

Trade name: Ultra Setting Vaporizer

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

64-17-5 ethanol

Printing date 02/27/2018

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

64-17-5 ethanol

#### · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms



· Signal word Danger

Hazard state	ements	
H222-H229	Extremely flammable aerosol. Pressurized container: May burst if heated.	
H319	Causes serious eye irritation.	
Precautiona	ary statements	
P102	Keep out of reach of children.	
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.	
P211	Do not spray on an open flame or other ignition source.	
P251	Pressurized container: Do not pierce or burn, even after use.	
P305+P351	+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if	
	present and easy to do. Continue rinsing.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.	

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

Does not contain Carbons (CKW)

Does not contain Fluorcarbons (FCKW)

Test pressure the used cane. 174 lb/sq in

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Section Product Safty
- · Contact: Mr.Lüth
- · Date of preparation / last revision 02/27/2018 / 2
- · Abbreviations and acronyms:

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

(Contd. on page 8)



Printing date 02/27/2018

Version: 3

Reviewed on 02/27/2018

Trade name: Ultra Setting Vaporizer

(Contd. of page 7)

HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Aerosol 1: Aerosols – Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A